

## Easy Re-Order Sheet For Your Falcon 4D+ Barcode Printer

Thermal Transfer Ribbon - Thermal Labels



### Thermal Transfer Ribbon Rating Scale: 1 = lowest performance, 5 = highest performance

| Width/Length | Part Number  | Formulation | Uncoated Paper | Coated Paper | Synthetics | Polys | Kimdura | Styrene |
|--------------|--------------|-------------|----------------|--------------|------------|-------|---------|---------|
| 1.57"/984'   | CFB0403004D  | Wax         | 2              | 4            |            |       |         |         |
| 2.36"/984'   | CFB0603004D  | Wax         | 2              | 4            |            |       |         |         |
| 3.15"/984'   | CFB0803004D  | Wax         | 2              | 4            |            |       |         |         |
| 3.5"/984'    | CFB0893004D  | Wax         | 2              | 4            |            |       |         |         |
| 4.02"/984'   | CFB1023004D  | Wax         | 2              | 4            |            |       |         |         |
| 4.33"/984'   | CFB1103004D  | Wax         | 2              | 4            |            |       |         |         |
| 4.33"/1476'  | CFB110450ZE  | Wax         | 2              | 4            |            |       |         |         |
| 1.57"/984'   | CF3000040300 | Resin       |                |              | 5          | 5     | 5       | 5       |
| 2.36"/984'   | CF3000060300 | Resin       |                |              | 5          | 5     | 5       | 5       |
| 3.15"/984'   | CF3000080300 | Resin       |                |              | 5          | 5     | 5       | 5       |
| 3.50"/984'   | CF3000089300 | Resin       |                |              | 5          | 5     | 5       | 5       |
| 4.02"/984'   | CF3000102300 | Resin       |                |              | 5          | 5     | 5       | 5       |
| 4.33"/984'   | CF3000110300 | Resin       |                |              | 5          | 5     | 5       | 5       |

### Thermal Labels (Non-perforated Labels Also Available) TT = Thermal Transfer, DT = Direct Thermal

| Mode         | Part Number      | Style                   | Width (in) | Length (in) | Labels per roll/stack | Rolls/Stacks per case |
|--------------|------------------|-------------------------|------------|-------------|-----------------------|-----------------------|
| TT           | CT400200F6000C3  | Fan-Folded              | 4          | 2           | 6000                  | 2                     |
| TT           | CT400300F4000C3  | Fan-Folded              | 4          | 3           | 4000                  | 2                     |
| TT           | CT400600F2000C3  | Fan-Folded              | 4          | 6           | 2000                  | 2                     |
| TT           | CT400650F2000C3  | Fan-Folded              | 4          | 6.5         | 2000                  | 2                     |
| DT           | CD400600F2000C3  | Fan-Folded              | 4          | 6           | 2000                  | 2                     |
| DT (1" core) | CD400300P500C1   | Perf. 4" O.D. wound out | 4          | 3           | 500                   | 16                    |
| DT (1" core) | CD400600P250C1   | Perf. 4" O.D. wound out | 4          | 6           | 250                   | 16                    |
| DT           | CD400600PF2000C3 | Perforated Premium      | 4          | 6           | 2000                  | 2                     |

Top View



Moveable Sensor



Inside View

