

## Easy Re-Order Sheet For Your Falcon 8 Barcode Printer

Thermal Transfer Ribbon

Thermal Labels



### Thermal Transfer Ribbon

| Width/Length | Part Number         | Formulation          | Uncoated Paper | Coated Paper | Synthetics | Polys |
|--------------|---------------------|----------------------|----------------|--------------|------------|-------|
| 4.72"/984'   | <b>BR85120300DE</b> | Wax (resin enhanced) | ■              | ■            | ▲          |       |
| 6.30"/984'   | <b>BR85160300DE</b> | Wax (resin enhanced) | ■              | ■            | ▲          |       |
| 8.66"/984'   | <b>BR85220300DE</b> | Wax (resin enhanced) | ■              | ■            | ▲          |       |
| 4.72"/984'   | <b>BR85120300DP</b> | Wax/Resin            | ■              | ■            | ■          |       |
| 6.30"/984'   | <b>BR85160300DP</b> | Wax/Resin            | ■              | ■            | ■          |       |
| 8.66"/984'   | <b>BR85220300DP</b> | Wax/Resin            | ■              | ■            | ■          |       |
| 4.72"/984'   | <b>BR85120300DS</b> | Resin                |                | ■            | ■          | ■     |
| 6.30"/984'   | <b>BR85160300DS</b> | Resin                |                | ■            | ■          | ■     |
| 8.66"/984'   | <b>BR85220300DS</b> | Resin                |                | ■            | ■          | ■     |

### Thermal Labels (Non-perforated & Color Labels Also Available) TT = Thermal Transfer, DT = Direct Thermal

| Mode              | Part Number             | Style                  | Width (in) | Length (in) | Labels per roll/stack | Rolls/Stacks per case |
|-------------------|-------------------------|------------------------|------------|-------------|-----------------------|-----------------------|
| TT (3" core)      | <b>CT400100P5500C3</b>  | Perforated             | 4          | 1           | 5500                  | 4                     |
| TT (3" core)      | <b>CT400200P3000C3</b>  | Perforated             | 4          | 2           | 3000                  | 4                     |
| TT (3" core)      | <b>CT400250P2400C3</b>  | Perforated             | 4          | 2.5         | 2400                  | 4                     |
| TT (3" core)      | <b>CT400300P2000C3</b>  | Perforated             | 4          | 3           | 2000                  | 4                     |
| TT (3" core)      | <b>CT400400P1500C3</b>  | Perforated             | 4          | 4           | 1500                  | 4                     |
| TT (3" core)      | <b>CT400500P1200C3</b>  | Perforated             | 4          | 5           | 1200                  | 4                     |
| TT (3" core)      | <b>CT400600P1000C3</b>  | Perforated             | 4          | 6           | 1000                  | 4                     |
| TT (3" core)      | <b>CT400650P1000C3</b>  | Perforated             | 4          | 6.5         | 1000                  | 4                     |
| TT (3" core)      | <b>CT400800P750C3</b>   | Perforated             | 4          | 8           | 750                   | 4                     |
| TT (3" core)      | <b>CT4001200P500C3</b>  | Perforated             | 4          | 12          | 500                   | 4                     |
| TT (3" core)      | <b>CT4001300P500C3</b>  | Perforated             | 4          | 13          | 500                   | 4                     |
| TT (3" core)      | <b>CT500300P2000C3</b>  | Perforated             | 5          | 3           | 2000                  | 4                     |
| TT (3" core)      | <b>CT600400P1500C3</b>  | Perforated             | 6          | 4           | 1500                  | 4                     |
| TT                | <b>CT400200F6000C3</b>  | Fan-Folded             | 4          | 2           | 6000                  | 2                     |
| TT                | <b>CT400300F4000C3</b>  | Fan-Folded             | 4          | 3           | 4000                  | 2                     |
| TT                | <b>CT400600F2000C3</b>  | Fan-Folded             | 4          | 6           | 2000                  | 2                     |
| TT                | <b>CT400650F2000C3</b>  | Fan-Folded             | 4          | 6.5         | 2000                  | 2                     |
| TT                | <b>CT600400F3000C3</b>  | Fan-Folded             | 6          | 4           | 3000                  | 1                     |
| DT (3" core)      | <b>CD400200P3000C3</b>  | Perforated             | 4          | 2           | 3000                  | 4                     |
| DT (3" core)      | <b>CD400300P2000C3</b>  | Perforated             | 4          | 3           | 2000                  | 4                     |
| DT (3" core)      | <b>CD400400P1500C3</b>  | Perforated             | 4          | 4           | 1500                  | 4                     |
| DT (3" core)      | <b>CD400600P1000C3</b>  | Perforated             | 4          | 6           | 1000                  | 4                     |
| DT (3" core)      | <b>CD400650P1000C3</b>  | Perforated             | 4          | 6.5         | 1000                  | 4                     |
| DT (3" core/8"OD) | <b>CD400200PP3000C3</b> | Perforated (wound out) | 4          | 2           | 3000                  | 4                     |
| DT (3" core/8"OD) | <b>CD400600PP1000C3</b> | Perforated (wound out) | 4          | 6           | 1000                  | 4                     |
| DT (3" core/8"OD) | <b>CD400650PP1000C3</b> | Perforated (wound out) | 4          | 6.5         | 1000                  | 4                     |
| DT                | <b>CD400600F2000C3</b>  | Fan-Folded             | 4          | 6           | 2000                  | 2                     |
| DT                | <b>CD400600PF2000C3</b> | Fan-Folded             | 4          | 6           | 2000                  | 2                     |